

Power Divider

138-960 MHz



Product Features

- Wide Frequency Bands
- Analog/P25/2G/3G/4G/LTE Coverage
- Low VSWR & Insertion Loss
- High Isolation
- Indoor & Outdoor, IP65
- Widely used for In-building Solutions

Specifications

Model Number	PD-138/960-50-2	PD-138/960-50-3	PD-138/960-50-4
Frequency Range	138-960 MHz		
Input Port Number	1		
Output Port Number	2	3	4
Splitter Loss	3.0 dB	4.8 dB	6.0 dB
Insertion Loss	0.7 dB	≤1.6 dB	≤1.8 dB
Isolation	20 dB Min.	18 dB Min.	16 dB Min.
VSWR	≤1.3:1	≤1.3:1	≤1.35:1
Total Input Power	50		
Impedance	50 ohm		
Connector	N-female		
Color	Black		
Temperature Range	-30 °C to +70 °C, -22 °F to +158 °F		
Application	Indoor or Outdoor, IP65		
Dimensions	6.5 x 5.0 x 1.0 In. (158 x 122 x 24 mm)	5.0 x 6.5 x 1.0 In. (122 x 158 x 24 mm)	5.0 x 6.5 x 1.0 In. (122 x 158 x 24 mm)
Weight	1.8 lbs (0.80 kg)	1.9 lbs (0.84 kg)	2.0 lbs (0.88 kg)

birdrf.com/products

The **RF** Experts | USA Sales : 30303 Aurora Rd, Solon, OH 44139 | www.birdrf.com

Phone: +1 440.248.1200 / 866.695.4569 [Toll Free] | Fax: +1 440.248.5426 / 866.546.4306 [Toll Free]